

GUANTE EN NYLON RECUBIERTO CON POLIURETANO

- **Descripción:** Guante en nylon recubierto con poliuretano
- **Marca:** Creator
- **Presentación comercial:** Empaque por par.
- **Fabricación:** Producto Importado
- **Color:** Negro

TALLA 7 REFERENCIA C20180047

TALLA 8 REFERENCIA C20180048

TALLA 9 REFERENCIA C20180049

TALLA 10 REFERENCIA C20180050



Descripción del producto

- Protegen las manos en actividades donde hay exposición a manipulación de elementos como cajas, cargas, papel, cartón.
- Bajo Estándar: CE Estándar Europeo EN388

Características del producto

- Excelente nivel de agarre, destreza y comodidad.
- Para uso personal.
- Reusable

Especificaciones del producto

- Guante tejido
- Compuesto: Nylon 100 %, Recubierto 100 % Poliuretano.

Aplicaciones

Usado en tareas generales y todo tipo de industria donde existan tareas de abrasión baja, como limpieza de residuos o Inspección.



Condiciones de Almacenamiento

- Humedad relativa máxima: 70%
- Temperatura máxima: 32°C
- Almacenar en un lugar fresco y seco, evitando los rayos directos del sol.
- Inadecuadas condiciones de almacenamiento, carga y descarga brutal probablemente afectasen la calidad de los productos.

Disposición Final

- En caso de que el producto se encuentre contaminado con residuos, colóquelo en el respectivo contenedor según cual sea la sustancia o material.
- Los empaques contenedores deberán ser depositada en el contenedor correspondiente a residuos reciclables, en caso que esta se encuentre contaminada por alguna sustancia o material, deséchela en el mismo contenedor donde se depositen estas sustancias

GARANTIA LIMITADA

CREATTOR garantiza que sus productos están libres de defectos en los materiales y en la mano de obra. Un producto sujeto a un reclamo de garantía se debe poner primero a disposición de un distribuidor CREATTOR autorizado o del vendedor a través del cual se ha adquirido el producto.





EU-TYPE EXAMINATION CERTIFICATE



The following model of Personal Protective Equipment has been subjected to an EU-type examination in accordance with the module B of the PPE regulation (2016/425) and has been shown to satisfy to essential health and safety requirements.

Certificate N° 0075/2394/162/11/19/3368

Issued by CTC, Notified Body N°0075, to the following model of personal protective equipment :

Description

PPE Type : *protective glove against mechanical risks*

Product reference : PU300

Article code : /

Glove description : 13G black nylon liner with PU PALM coating

Available sizes : 6/XS 7/S 8/M 9/L 10/XL 11/XXL

Pictures :



Reference standard :

Levels of performance / class of protection

EN 420:2003+A1:2009

-

EN 388:2016

4 1 3 1 X

« X » indicates that the glove has not been submitted to the test or the test method appears not to be suitable for the glove design or material.

At the date of certificate the product is in compliance with Annex XVII of REACH regulation (n° 1907/2006 and revisions)

Full description of the PPE, reference rules verified in the context of the EU-type examination and information given on the product are detailed in the manufacturer's technical file and the Instruction for Use index 01 dated from November 2019

NOTA : Any modification to new items of the personal protective equipment object of this EU type approval certificate or any modification of the information contained in the manufacturer technical file which served for the deliverance of the EU type approval certificate (change of address, change of company status) should be brought to the attention of the notified body in accordance with Annex V §7.2 of Regulation 2016/425.

Issued in Lyon by
Maxence DREVET
 Project Certification Manager

Date of first issue : 18 November 2019
End of validity date : 18 November 2024



Original CTC



In application of the Regulation 2016/425 of the European parliament and the Council of 16th March 2016 related to Personal Protective Equipment and repealing the Directive 89/686/EEC.

www.ctcgroupe.com

cemarking@ctcgroupe.com

CTC - 4, rue Hermann Frenkiel - 69367 Lyon cedex 07 - France
Tél : +33 (0)4 72 76 10 10 - Fax : +33 (0)4 72 76 10 00 - ctc@ctcgroupe.com

Comité Professionnel de Développement Économique (CPDE) Cuir Chaussure Maroquinerie Ganterie
Loi 78-654 du 22.06.1978 - Siret: 77564972600160 - Code NAF 9412Z - TVA FR 80775649726

MANUFACTURER'S TECHNICAL FILE TO THE PPE REGULATION 2016/425

Reference of the product	:	PU300
Article code	:	/
Technical file index	:	01
Last update	:	November 2019

GLOVE DESCRIPTION

General glove description :

13G black nylon liner with PU PALM coating
type of coating finish : smooth

Visual description (picture back and palm sides) :



Field of use

Transportation/small parts handling/equipment handling for mechanical risks

Risk assessment (Essential Health and Safety Requirement. Annex II - PPE Regulation)			
		Applicable	Covered by
§1	Requirements defined in the Annex II §1 are applicable to all PPE	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/> Standard <input checked="" type="checkbox"/> Instruction for use <input checked="" type="checkbox"/> Marking
§1.4	Manufacturer's instructions and information is available	<input checked="" type="checkbox"/>	<input type="checkbox"/> Standard <input checked="" type="checkbox"/> Instruction for use <input type="checkbox"/> Marking
§2.5	PPE which may be caught up during use	<input checked="" type="checkbox"/>	<input type="checkbox"/> Standard <input checked="" type="checkbox"/> Instruction for use <input type="checkbox"/> Marking
§2.12	PPE bearing one or more identification markings or indicators directly or indirectly relating to health and safety	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/> Standard <input checked="" type="checkbox"/> Instruction for use <input checked="" type="checkbox"/> Marking
§3.3	The PPE is intended to protect against mechanical injuries	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/> Standard <input checked="" type="checkbox"/> Instruction for use <input checked="" type="checkbox"/> Marking

Available sizes :

Minimum length of glove (mm)	Sizes
220	6/XS
230	7/S
240	8/M
250	9/L
260	10/XL
270	11/XXL

Glove constitution :

	Reference	Color	Material	Surfacic mass (g/m ²)	Gauges	Thickness
Palm		Black	PU	244g/m ²		0.088mm
		Black	Nylon	188g/m ²	13G	
Back		Black	Nylon	188g/m ²	13G	
Cuff		Black	Nylon + Elastic	268g/m ²	13G	
Binding		Yellow / Brown / Red / White / Black / Dark Blue	Polyester			

PROTECTION SCOPE

This glove meets the essential requirements of the Personal Protective Equipment Regulation 2016/425.
This glove is designed against mechanical risks.
It is a category II product.

GENERAL REQUIREMENTS

Standard EN 420 : 2003 + A1 : 2009

Dexterity : 5

Size : conform

At the date of certificate the product is in compliance with Annex XVII of REACH regulation (n° 1907/2006 and revisions)

SPECIFIC REQUIREMENTS AND PERFORMANCE LEVELS

Mechanical hazard EN 388 : 2016

Protection offered	Performance levels
Abrasion resistance	4
Blade cut resistance	1
Tear strength resistance	3
Puncture resistance	1
Cut Resistance method (EN ISO 13997)	X
Impact Protection	-

The levels of performance have been measured on the palm

« X » indicates that the glove has not been submitted to the test or the test method appears not to be suitable for the glove design or material.

TEST REPORTS

Laboratory	CTC	Other
EN 420 + innocuousness	S160301159_2 S160301161_2 S160302013_1 S181217027_1(DMFU)	
EN 388	S181217027_1 S160301159_2	

MARKING - PACKAGING

Information printed on the glove :

Logo of Manufacturer :

Logo 

Glove's reference : PU300

Article Code : /

Size indicator

Pictograms related to risks against which protection is offered with performance levels

Information pictogram

Address of Manufacturer :

Date of Manufacture (month/year) and/or Serial number :

Marking example :



Method of marking on the glove :

the label sewing in the overlock

Packaging :

12 pairs in the poly bag

PPE subject to ageing :

The design performance can not be significantly affect by ageing when stored in appropriate conditions (humidity, temperature, clean , ventilated, light).

Declaration of conformity :

Available with product.

MEANS OF CONTROL

First,when the gloves are still half finished, we measure the weight by per dozen.If there are some gloves cannot achieve the standard, they will be sent to reproduce.

Then,we will exam to see the smoothness and flatness of the glove' surface.

The following step is viscosity tests and length tests.The tests are very strict so that we can ensure the quality.

After everything prepared, we may start to produce the gloves consulting and following the sanple.

Then,we pick out 4%-5% gloves from the total number and leak out the unqualified products.

Finally,we put the gloves(in carton)to our warehouse,we will ask our QC to check the gloves in the warehouse according to the proportion(maybe 3%).If we find the result cannot achieve the standard,then we will ask workers tore package,and check again by QC.

We will shipped the gloves after we checked ok!

After our customer received gloves,they will also check and then give us the report!

We test the quality of gloves every three months according to EN388 and EN420.

For EN388 test:at present, we have machines in our own laboratory.When we beginning a new order,then we will have test firstly by ourself,it will control our quality better.

For EN420 test:we asked our vendor to according to the request,and the will not use any materials which contain Hazardous Substances.when the materials come to our factory, we will check again

INSTRUCTION FOR USE



CHINA
Glove reference : PU300
Article code: /
User notice index : 01
Last update : November 2019
Available sizes : 6/XS 7/S 8/M 9/L 10/XL 11/XXL

Glove description :

13G black nylon liner with PU PALM coating

THIS GLOVE IS A PERSONAL PROTECTIVE EQUIPMENT BELONGING TO THE CATEGORY II.

It meets the requirements of the PPE Regulation 2016/425 applicable from April 21th, 2018 : innocuousness, comfort, solidity.

It has been subject to a UE-type Examination performed by :

C.T.C. (0075)
4, rue Hermann Frenkel
69367 LYON Cedex 07
FRANCE


Applicable standards :

The glove meets the requirements of the standard EN 420 : 2003 + A1 : 2009 « General requirements for work glove ». Dexterity : 5

Moreover, this glove has been designed for the following applications :

Application :

Mechanical hazard - EN 388 : 2016



4 1 3 1 X

Levels of performance

Abrasion resistance	4	(on 4 maxi)
Blade cut resistance	1	(on 5 maxi)
Tear resistance	3	(on 4 maxi)
Puncture resistance	1	(on 4 maxi)
Cut Resistance method (EN ISO 13997)	X	(A to F)
Impact Protection		

« X » indicates that the glove has not been submitted to the test or the test method appears not to be suitable for the glove design or material.

Protection limit :

Users should be warned that gloves should not be worn when there is a risk of entanglement by moving parts of machines.

This model does not contain any substances at levels that are known to, or suspected to, adversely affect user hygiene or health.

The protection against risks or hazards which are not mentioned in this document is not warranted.

The levels of performance mentioned are only valid for the palm of the glove.

The levels of performance mentioned are only valid for new gloves, not washed, nor regenerated.

These levels of performance are obtained from the tests done according to conditions defined by the applicable standards.

This glove shall not be in contact with fire

Before use, the glove shall be visually controlled, in case of deterioration the gloves must be scrapped (abrasion, cut, tear, ...).

For gloves with different layers of material, the performance levels are warranted only for the whole glove.

For gloves with two or more layers the overall classification does not necessarily reflect the performance of the outermost layer.

Storage and cleaning notice

Keep in its original packaging, under ordinary temperature and humidity conditions and in clean, covered and ventilated premises.

PPE subject to ageing :

The design performance can not be significantly affect by ageing when stored in appropriate conditions (humidity, temperature, clean , ventilated, light).

Declaration of conformity :

Available with product.